

PALM-3615 US P

UNITED STATES PATENT APPLICATION FOR

COMMUNICATION PROTOCOL FOR WIRELESS DATA
EXCHANGE VIA A PACKET TRANSPORT BASED SYSTEM

Inventors:

Hatem Oueslati and
Ludovic Ferrandis

Prepared by:

WAGNER, MURABITO & HAO LLP
TWO NORTH MARKET STREET
THIRD FLOOR
SAN JOSE, CALIFORNIA 95113
(408) 938-9060

COMMUNICATION PROTOCOL FOR WIRELESS DATA
EXCHANGE VIA A PACKET TRANSPORT BASED SYSTEM

BACKGROUND OF THE INVENTION

5 FIELD OF THE INVENTION

The present invention relates to the field of electronic communication. More specifically, embodiments of the present invention relate to a communication protocol for short messaging wireless communication.

10 RELATED ART

As the components required to build a computer system have reduced in size, new categories of electronic devices and computer systems have emerged. One of the new categories of computer systems is the "palmtop" computer system. A palmtop computer system is a computer that is small enough to be held in the hand of a user and can therefore be "palm-sized." Most palmtop computer systems are used to implement various Personal Information Management (PIM) applications such as an address book, a daily organizer (calendar, datebook, etc.) and electronic notepads, to name a few. Palmtop computers with PIM software have been known as Personal Digital Assistants (PDAs). Many PDAs have a small and flat display screen associated therewith.

User convenience and device value are very important factors for portable electronic devices. Typically, portable electronic devices are employed while the user is on the run, e.g., in business meetings, on business

travel, personal travel, in a vehicle, on foot, etc. Because the user may be occupied or busy while using the portable electronic device, the number of user steps or user tasks required in order to access information from an electronic device (or to store information into the electronic device) is crucial for producing a commercially successful and useful product. That is, the more difficult it is to access data from an electronic device, the less likely the user will perform those tasks to obtain the information. Likewise, the easier information is to obtain, the more likely the portable electronic device will be used to obtain that information and the more likely the portable electronic device will become a part of the user's everyday activities.

Similarly, the more useful the device, the more the device will be used and acquired. The functionality of mobile wireless devices is undergoing a transition. Mobile devices are evolving from a single application device with dedicated specific purpose communication channel (for example, a cell phone or pager), to more general-purpose devices with more flexible data communication capabilities.

More specifically, wireless technology is advancing, both in the number of options that are available for providing connectivity, and in their flexibility to provide general purpose data communication. Different technologies such as GSM with Short Message Service (SMS), NBS (NarrowBand Sockets), cellular technologies (e.g., CDMA, TDMA), LAN access technologies (e.g., IEEE 802.11, HomeRF) and PAN technologies (e.g., Bluetooth, IR), each address a different set of needs, and provide different set of potential services. Mobile devices are

no longer also restricted to one communication channel. Modular mobile devices allow network interfaces to be attached, allowing for unlimited communications configurations. The SMS system allows short messages and/or other data to be wirelessly communicated between devices. Bluetooth technology allows a single mobile device to be simultaneously in access multiple piconets through a single interface.

Many different applications are currently being developed for portable computer systems in order to make use of the wireless communication features offered for these platforms. Some applications are designed for sending information between two or more portable computer systems. However, there do not exist today communication protocols designed for use on portable computer systems that can provide efficient communication between the devices.

What is desired is an efficient protocol to ensure that the proper application receive, or be notified of, desired data that was received by a device. The NBS standard mentioned above, from Nokia and Intel, is not fully appropriate for the needs of a portable computer system having limited computing resources. For instance, with NBS, if an application is to exchange its data wirelessly with another portable device, some registration needs to be done against an organization in order to obtain a unique identification for the type of data that is being exchanged. This is required for each of potentially many applications, thereby adding overhead and complexity to the communication system, which is not advantageous for a portable computer

[illegible]

SUMMARY OF THE INVENTION

Accordingly, what is needed is a wireless communication protocol that can be used between two or more computer systems that is flexible, not complex, and that is transparent of the transport being used. What is further needed is an efficient communication protocol that can be used between two or more portable computer systems each having limited computing resources and narrow bandwidth communication capabilities. What is also needed is such a system that also allows a sending application (residing on one computer system) to send information to another application (residing on a different computer system) in such a way that the underlying protocol is transparent to the sending application. What is needed yet is such a system that is also transparent to the user. Embodiments of the present invention provide the above advantages and others not specifically mentioned above but described in the sections to follow.

A protocol is described herein for wireless data exchange via a packet transport based system. The protocol may be used in conjunction with two or more portable computer systems. One of the portable computer systems may be a personal digital assistant (PDA) having an internal wireless communication unit, e.g., a GSM radio using the Short Message Service (SMS). In an alternative embodiment, one or both of the computer systems may be a PDA connected to a wireless device having the GSM radio functionality therewithin, e.g., such as a cell phone connected to (e.g., via wired or wireless link) a PDA. The protocol can be used by a sending application residing on the portable computer system to transparently send a wireless message to a receiving computer system. The packet is then automatically routed to the proper destination application residing

on the receiver. The protocol uses a special token identifier that is placed before a data type identifier. The data type identifier is used by the receiver, in conjunction with an application registry, to determine the proper destination application. The data type identifier can identify by extension, MIME type or by application creator, for instance. The flexible protocol offers application developers an opportunity to write wireless data exchanging applications in which the communication mechanism is transparent to the application. The protocol is transport-independent and compliant with current smart messaging devices (as an extension of NBS).

More specifically, an embodiment of the present invention includes a communication protocol comprising the steps of: a) a sending application resident on a first computer system selecting a transport mechanism and passing data to a first utility program resident on the first computer system; b) the first utility program, adding a token, a data type category identifier, and a data type identifier to the data to form an information packet and then, transparently to the sending application, using the transport mechanism to transmit the information packet to a second computer system; c) a second utility program, resident on the second computer system, locating the data type identifier in the information packet using the token; d) the second utility program indexing a relevant category of an application registry with the data type identifier to determine a destination application that is associated with the data type identifier, wherein the application registry comprises identifiers categorized into a plurality of different data type categories and wherein the data type

category identifier of the information packet identifies the relevant category; and
e) supplying the data packet to the destination application.

Embodiments include the communication protocol and wherein the first
5 computer system and the second computer system are portable computer
systems. Embodiments include the communication protocol and wherein the
first computer system and the second computer system are each portable
computer systems connected to a separate wireless communication device.

Embodiments include the communication protocol and wherein the transport
10 mechanism is substantially compliant with the Short Message Service (SMS)
standard and wherein the transport mechanism includes the use of a GSM
wireless communication device.

Embodiments include the communication protocol and wherein the
15 plurality of data type categories comprise: an Extension category; a MIME type
category and an Application Creator category and wherein said data type
category identifier is a numeric value. Embodiments also include a
communication system implemented in accordance with the communication
protocol described above.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is system illustration of a palmtop or "palm sized" computer system connected to other computer systems and the Internet via a cradle device or via a wireless communication link.

5

Figure 2A is a top side perspective view of an exemplary portable computer system.

Figure 2B is a bottom side perspective view of the exemplary portable computer system of Figure 2A.

Figure 2C is a perspective top view of another embodiment of the exemplary portable computer system.

Figure 3 is a perspective view of a cradle device for connecting a palmtop computer system to other systems via a communication interface.

Figure 4 is a logical block diagram of an exemplary portable computer system in accordance with an embodiment of the present invention.

Figure 5A illustrates a wireless communication system in accordance with the present invention including a sending computer system (with internal wireless device) and a receiving computer system (with internal wireless device).

Figure 5B illustrates a wireless communication system in accordance with the present invention including a sending computer system (with external but connected wireless device) and a receiving computer system (with external but connected wireless device).

Figure 6A illustrates components of one embodiment of the present invention situated at the sending computer system.

10 Figure 6B illustrates components of one embodiment of the present invention situated at a sending computer system having an external but connected wireless device.

15 Figure 7 is a flow diagram indicating steps performed according to an embodiment of the communication protocol of the present invention at the sending computer system.

Figure 8A illustrates components of one embodiment of the present invention situated at the receiving computer system.

20

Figure 8B illustrates components of one embodiment of the present invention situated at the receiving computer system having an external but connected wireless device.

Figure 9 illustrates the use of the application registry and protocol tags to determine a destination application at the receiving computer system in accordance with an embodiment of the communication protocol of the present invention.

5

Figure 10 is a flow diagram indicating steps performed according to an embodiment of the communication protocol of the present invention at the receiving computer system.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the present invention, a protocol for wireless data exchange via a packet transport based system, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be recognized by one skilled in the art that the present invention may be practiced without these specific details or with equivalents thereof. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

NOTATION AND NOMENCLATURE

Some portions of the detailed descriptions which follow (e.g., processes 510 and 600) are presented in terms of procedures, steps, logic blocks, processing, and other symbolic representations of operations on data bits that can be performed on computer memory. These descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. A procedure, computer executed step, logic block, process, etc., is here, and generally, conceived to be a self-consistent sequence of steps or instructions leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated in a computer system. It has proven convenient at times, principally for reasons of

common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing terms such as "checking," "accessing" or "processing" or "computing" or "suspending" or "resuming" or "translating" or "calculating" or "determining" or "scrolling" or "displaying" or "recognizing" or "executing" or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

EXEMPLARY PALMTOP COMPUTER SYSTEM PLATFORM

The communication protocol and processes of the present invention described herein may be practiced on any computer system but are applicable to portable computer systems, e.g., personal digital assistants (PDA). These devices include, for instance, intelligent cell phones, computerized pagers and portable computer systems. Although applicable across a wide variety of platforms and devices, embodiments of the present invention are described herein by example with respect to a portable or mobile computer system.

Figure 1 illustrates an exemplary networked system 50 that can be used in conjunction with an embodiment of the present invention. System 50 is exemplary only and comprises a host computer system 56 which can either be a desktop unit as shown, or, alternatively, can be a laptop system 58. Optionally, one or more host computer systems can be used within system 50. Host computer systems 58 and 56 are shown connected to a communication bus 54, which in one embodiment can be a serial communication bus, but could be of any of a number of well known designs, e.g., a parallel bus, Ethernet Local Area Network (LAN), etc. Optionally, bus 54 (or a separate communication channel) can provide communication with the Internet 52 using a number of well known protocols.

Importantly, a communication link is also coupled to a cradle 60 (or cable dock) for receiving and initiating communication with an exemplary palmtop ("palm-sized") portable computer system 100 over line 265. Cradle 60 provides an electrical and mechanical communication interface between the computer system 100 for two way communications. In one embodiment, the communication link including cradle 60 and line 265 is a serial communication link or can be a USB link. Computer system 100 may also contain a wireless communication mechanism 64 for sending and receiving information to or from other devices. The wireless communication mechanism could be, for instance, a cellular phone (including a GSM , for instance), Bluetooth and/or wireless LAN (e.g., IEEE 802.11), or a combination of all, and these devices can be used to establish the communication link between the portable computer system 100

and the host computer system or between another portable computer system or server, etc.

Figure 2A is a perspective illustration of the top face 100a of one embodiment of a palmtop computer system. The top face 110a contains a display screen 105 surrounded by a bezel or cover. A removable stylus 80 is also shown. The display screen 105 contains a transparent touch screen (digitizer) able to register contact between the screen and the tip of the stylus 80. The stylus 80 can be of any material to make contact with the screen 105. As shown in Figure 2A, the stylus 80 is inserted into a receiving slot or rail 350. Slot or rail 350 acts to hold the stylus when the computer system 100a is not in use. Slot or rail 350 may contain switching devices for automatically powering down and automatically power up computer system 100a based on the position of the stylus 80. The top face 100a also contains one or more dedicated and/or programmable buttons 75 for selecting information and causing the computer system to implement functions. Other buttons (icons) can be implemented within a silk screen layer material 84 on which regions 106a and 106b reside. An exemplary on/off button 95 is also shown.

Figure 2A also illustrates a handwriting recognition pad or "digitizer" containing two regions 106a and 106b. Region 106a is for the drawing of alpha characters therein for automatic recognition (and generally not used for recognizing numeric characters) and region 106b is for the drawing of numeric characters therein for automatic recognition (and generally not used for recognizing numeric characters). The stylus 80 is used for stroking a character

within one of the regions 106a and 106b. The stroke information is then fed to an internal processor for automatic character recognition. Once characters are recognized, they are typically displayed on the screen 105 for verification and/or modification.

5

The digitizer 160 records both the (x, y) coordinate value of the current location of the stylus and also simultaneously records the pressure that the stylus exerts on the face of the digitizer pad. The coordinate values (spatial information) and pressure data are then output on separate channels for
10 sampling by the processor 101 (Figure 4). In one implementation, there are roughly 256 different discrete levels of pressure that can be detected by the digitizer 106. Since the digitizer's channels are sampled serially by the processor, the stroke spatial data are sampled "pseudo" simultaneously with the associated pressure data. The sampled data is then stored in a memory by the
15 processor 101 (Figure 4) for later analysis.

Figure 2B illustrates the bottom side 100b of one embodiment of the palmtop computer system. An optional extendible antenna 85 is shown and also a battery storage compartment door 90 is shown. A communication
20 interface 108 is also shown. In one embodiment of the present invention, the serial communication interface 108 is a serial communication port, but could also alternatively be of any of a number of well known communication standards and protocols, e.g., parallel, SCSI, Firewire (IEEE 1394), Ethernet, etc. In Figure 2B is also shown the stylus receiving slot or rail 350.

Figure 2C illustrates a front perspective view of another implementation 100c of the palmtop computer system. As shown, the flat central area is composed of a display screen area 105 and a thin silk screen layer material portion 84. Typically, the silk screen layer material portion 84 is opaque and may contain icons, buttons, images, etc., graphically printed thereon in addition to regions 106a and 106b. The display screen area 105 and portion 84 are disposed over a digitizer.

Figure 3 is a perspective illustration of one embodiment of the cradle 60 for receiving the palmtop computer system 100. In other embodiments, cradle 60 is not a stand-up device but is rather part of a cable connection between the palmtop computer system 100 and the desk top unit. Cradle 60 contains a mechanical and electrical interface 260 for interfacing with serial connection 108 (Figure 2B) of computer system 100 when system 100 is slid into the cradle 60 in an upright position. Alternatively, a USB connection could be used. Once inserted, button 270 may be pressed to initiate two way communication between system 100 and other computer systems coupled to serial communication 265.

Figure 4 illustrates circuitry of portable computer system 100. Computer system 100 includes an address/data bus 99 for communicating information, a central processor 101 coupled with the bus 99 for processing information and instructions, a volatile memory 102 (e.g., random access memory RAM) coupled with the bus 99 for storing information and instructions for the central processor

101 and a non-volatile memory 103 (e.g., read only memory ROM) coupled with the bus 99 for storing static information and instructions for the processor 101. Computer system 110 also includes an optional data storage device 104 (e.g., thin profile removable memory) coupled with the bus 99 for storing information and instructions. Device 104 can be removable. As described above, system 100 also contains a display device 105 coupled to the bus 99 for displaying information to the computer user.

Also included in computer system 100 of Figure 4 is an alphanumeric input device 106 which in one implementation is a handwriting recognition pad ("digitizer") having regions 106a and 106b (Figure 2A), for instance. Device 106 can communicate information (spatial data and pressure data) and command selections to the central processor 101.

System 110 also includes an optional cursor control or directing device 107 coupled to the bus for communicating user input information and command selections to the central processor 101. In one implementation, device 107 is a touch screen device (also a digitizer) incorporated with screen 105. Device 107 is capable of registering a position on the screen 105 where the stylus makes contact and the pressure of the contact. The digitizer can be implemented using well known devices, for instance, using the ADS-7846 device by Burr-Brown that provides separate channels for spatial stroke information and pressure information.

The display device 105 utilized with the computer system 100 may be a liquid crystal device, cathode ray tube (CRT), field emission device (FED, also called flat panel CRT) or other display device suitable for creating graphic images and alphanumeric characters recognizable to the user. Any of a number of display technologies can be used, e.g., LCD, FED, plasma, etc., for the flat panel display 105. In one embodiment, the display 105 is a flat panel multi-mode display capable of both monochrome and color display modes.

Signal communication device 108, also coupled to bus 99, can be a serial port (or USB port) for communicating with the cradle 60. In addition to device 108, wireless communication links can be established between the device 100 and a host computer system (or another portable computer system) using a Bluetooth wireless device 360, an infrared device 355, or a GSM radio device 240. Device 100 may also include a wireless modem device 240 and/or a wireless radio, e.g., a GSM wireless radio with supporting chipset. The wireless modem device 240 is coupled to communicate with the processor 101 but may not be directly coupled to port 108.

In one implementation, the Mobitex wireless communication system may be used to provide two way communication between system 100 and other networked computers and/or the Internet via a proxy server. In other embodiments, TCP protocol can be used or SMS can be used. System 100 of Figure 4 may also contain batteries for providing electrical power. Replaceable cells or rechargeable batteries can be used. Well known electronics may be

coupled to the battery to detect its energy level and this information can be sampled by the processor 101.

WIRELESS COMMUNICATION PROTOCOL

5 OF THE PRESENT INVENTION

Figure 5A illustrates a communication system 440 in accordance with one embodiment of the present invention. System 440 includes a first computer system 410 and a second computer system 420 which are connected together via a wireless communication link 430. The computer systems could be of any
10 type, but in one embodiment they are portable computer systems, e.g., hand-held computer systems. The wireless link 430 may be established using a number of different mechanisms, e.g., GSM wireless radio, Bluetooth, IR, wireless LAN, cellular, etc. The wireless link 430 may use any wireless communication protocol, but in one exemplary embodiment, the Short Message
15 Service (SMS) communication protocol is used.

The first computer system 410 contains a GSM chipset 240a and a number of different application programs 415. Likewise, the second computer system 420 contains a GSM chipset 240b and a number of different application
20 programs 425. In accordance with one example of the present invention, it is assumed that the first computer system 410 is the sender and the second computer system 420 is the receiver.

Figure 5B illustrates another embodiment of the present invention 440'
25 where one or more of the computer systems utilize an external, but connected

wireless communication device 240c, e.g., a cell or mobile phone. This is different from the one-piece solution described in Figure 5A. Computer system 410' can be connected to the wireless device 240c using a number of different wired or wireless communication channels, e.g., by IR, or BT, or serial interface, or by a USB connection. It is appreciated that all aspects of the present invention discussed herein are equally applicable to the embodiments where the wireless device is placed internal to the PDA ("one-piece solution") or, alternatively, disposed external to the PDA ("two-piece solution") but connected to it via some wired or wireless communication channel. Therefore, the term "computer system" used herein anticipates both the one-piece and the two-piece systems. Further, the invention covers the embodiment where a one-piece system is communicating with a two-piece system and vice-versa.

Sender Side. Figure 6A illustrates components that are used in the sending phase of the communication protocol of the present invention and Figure 7 is a flow diagram of steps implemented in the sending phase of the communication protocol. Figure 6B illustrates an embodiment where the computer system includes an external wireless communication device, e.g., a mobile phone.

Reference is made to Figure 6A and Figure 7. Process 510 is implemented as computer code stored in memory and executed over a processor. According to the sending phase of the protocol, at step 515, an application program of the first computer system generates data to be sent to the second computer system. At step 520, the application forwards the data to a

transport handler program which is a utility application and specifies which transport type to use, e.g., SMS. At step 525, the transport handler program 450a (Figure 6A) of the first computer system calls the corresponding transport library which adds places certain protocol tags in the data to obtain an

5 information packet. The information packet includes the data, a token, a data type identifier and a category type identifier. These items are described further below.

A number of different utility programs can be used for this purpose. In

10 one embodiment of the present invention, an exchange manager 450a is used as the utility which is described in co-pending patent application serial number 09/598,670, entitled "Data Exchange Between a Handheld Device and Another Computer System Using An Exchange Manager via Synchronization," by Peacock, filed June 20, 2000, attorney docket PALM-3214 and assigned to the

15 assignee of the present invention and hereby incorporated by reference. The exchange manager is also described in co-pending patent application serial number 09/598,668, entitled "Information Exchange Between a Handheld Device and another Computer System Using An Exchange Manger and Uniform Resource Locator (URL) Strings," by Peacock, filed June 20, 2000,

20 attorney docket PALM-3215 and assigned to the assignee of the present invention and hereby incorporated by reference.

The exchange encoding scheme of the present invention first includes a token marking the beginning of the protocol header. The token can be any

25 identifier, e.g., in one embodiment it is: "//EXG." The category type identifier is a

number identifying the way to type the data content and is defined in one embodiment according to the following exemplary definitions:

- “1” : means that the data type is informed by its Extension;
- 5 “3”: means that the data type is informed by its Application Creator; and
- “2”: means that the data type is informed by its Mime Type.

The Mime category type is a well known data type category and defines the type of content that is found in the data. Exemplary Mime types include:

- 10 TEXT/PLAIN or TEXT for text files; TEXT/XML for XML specific pages;
 TEXT/HTML for Internet documents and web pages; /DIF for a data interchange
 file; IMAGE/JPEG for image or picture files and MPEG or VIDEO/MPEG for
 motion pictures, etc. The Extension category type is also a well known data
 type category and is a multiple character label associated with a datafile that
15 also indicates its content type. For instance, “.vcf” indicates a v-card extension,
 “.exe” indicates an executable file extension, “.bin” indicates a binary formatted
 file extension, “.txt or .doc” indicates a text or word processing file extension, etc.
 Lastly, the Application Creator category type is a well known data type category
 and is a four byte identifier that uniquely identifies the name of the application
20 program that created the data.

- It is appreciated that the protocol of the present invention is open and
 many more data type categories can be defined, in addition to, the three
 exemplary designations given above. In one embodiment, the values “4-255”
25 are reserved for category type identification.

Following the category type identifier, is a data type identifier that identifies more specifically the actual data type within the identified category. For instance, if the previous number was "1," it is the Extension category of the data type (for example "vcf" means a vCard extension). If the previous number was "2," it is the Mime type category of the data (for example "text/plain" means a Memo mime type). Lastly, if the previous number was "3" it is the target Application Creator (for example, 0x746F646F or 'todo' means that the receiving application for those data is the ToDo application). At last, the information packet may contain the ending of the protocol header: " " (a space), also called an ending token. In one embodiment, this ending token is mandatory.

The communication protocol of the present invention utilizes these protocol tags, described above, to identify an application on the receiving computer system that is to receive the data of the information packet. Using the protocol of the present invention, an application is provided with an easy way to perform wireless data exchanges between applications. For instance, the application need only put a very short header in front of its "real" data and the information packet is ready to go over the wireless transport.

The following illustrate some examples of the protocol tags in accordance with embodiments of the present invention. Assume the sending application wants to send vCards wirelessly (e.g., using the SMS standard as a transport) to another computer system. An exemplary vCard is shown below:


```
"BEGIN:VCARD\r\nVERSION:2.1\r\nN:Hatem;\r\nTEL;PREF;CELL:0499524300\r\nUID:7815169\r\nEND:VCARD\r\n".
```

- 5 The application merely places this short header in front of its payload data:

```
"//EXG1vcf ".
```

The result is an information packet that looks like the following:

10

```
"//EXG1vcf
BEGIN:VCARD\r\nVERSION:2.1\r\nN:Hatem;\r\nTEL;PREF;CELL:0499524300\r\nUID:7815169\r\nEND:VCARD\r\n".
```

- 15 The sending computer system uses SMS as the transport and it sends the information packet to the receiving computer which then receives the vCard wirelessly. Other applications, such as wireless games or wireless chat applications, or others, can be developed to use the exchange encoding scheme.

20

Returning to Figure 7, at step 530, the transport library segments data if needed and passes it the proper communication unit to use to transfer the data. In this process, a telephony manager can be used.

In the example of Figure 6A, the exchange manager may use a number of different transports, e.g., Bluetooth 360a, IR 355a or GSM 240a, or others at step 530 of Figure 7. The selection of the transport used may be performed transparent to the sending application. Alternatively, the sending application
5 may forward specific instructions for the exchange manager to use a particular communication mechanism. Assuming none is specified, the exchange manager will select the most appropriate transport available, in this case the GSM mechanism is selected and SMS is used. Once the selection is made, the exchange manager passes the information packet to the communication
10 mechanism selected.

At step 535 of Figure 7, the selected communication mechanism then uses the proper communication protocol to transmit the data packet wirelessly to the second computer system. It is appreciated that the communication
15 protocol of the present invention can also be used "as is" directly into SMS contents and the only condition that the transport layer provides segmentation capabilities (which is actually the case with SMS). The communication protocol of the present invention is also independent from the transport. In one
20 embodiment it is shown as being used over SMS, but it can run over any other packet transport having segmentation capabilities.

Figure 6B is analogous to Figure 6A, except the sending computer system 410' includes an externally coupled cell or mobile phone 240c. Also illustrated are the transport library 472a and the telephony manager 474a. The
25 mobile phone 240c can be communicatively coupled to the portable computer

via a number of different wired or wireless communication channels, including, for instance, BT, IR, USB or serial. Mobile device 240c then performs the wireless communication 430. It is appreciated that the process of Figure 7 equally applies to system 410' of Figure 6B.

5

Receiver Side. Figure 8A and Figure 9 illustrate components that are used in the receiving phase of the communication protocol of the present invention and Figure 10 is a flow diagram of steps implemented in the receiving phase of the communication protocol. Figure 8B illustrates an embodiment where the receiving computer system includes an external wireless communication device, e.g., a mobile phone.

10

The receiver computer system 420 contains a transport handler utility program, e.g., an exchange manager 450b. The receiver computer system 420 also contains receivers for several different transport mechanisms, e.g., GSM 240b, IR 355b and BT 360b. A number of application programs 415 are resident on the receiver 420 and also an application registry 470b is resident in the receiver 420.

15

As shown in Figure 9, the application registry 470b contains a mapping of data type identifiers to the applications that are registered for that data type. Also, the data type identifiers are organized by category. The first column 570 represents the "Extensions" category. The second column 575 represents the "Application Creator" category and the third column 580 represents the "Mime Type" category. The fourth column 585 represents the application name that

20

25

corresponds to a particular data type identifier of a particular category. One application may be associated with more than category. The use of the application registry is described further below.

5 Figure 10 illustrates a flow diagram of the receiving end of the communication protocol of the present invention. Process 600 is implemented as computer code stored in memory and executed over a processor. At step 610, the receiver, e.g., the GSM, obtains the information packet including the protocol tags. At step 615, the information packet is passed from the telephony
10 manager to the transport library of the receiving computer which examines the data type identifier and the data category identifier which follow the token, (e.g., “//EXG”), in the received information packet. At step 620, the data is reassembled, if necessary, and the data type identifier and the data category identifier are passed to the exchange manager 450b which references the
15 application registry to determine which application of applications 415 is the proper recipient for the data. This is also shown in Figure 8B.

 Figure 9 illustrates the manner in which this determination is made. At block 565, the exchange manager examines the category type identifier that
20 follows the token, e.g., “1,” “2,” or “3.”

 The category type identifier determines which data column will be used of the application registry to locate the recipient application. If “1” is found, then column 570 is used for the “Extensions category.” If “3” is found, then column
25 575 is used for the “Application Creator category.” If “2” is found, then column

580 is used for the "Mime Type category." Once the proper column is selected, then the exchange manager examines the data type identifiers of that column to find a match with the data type identifier located in the information packet.

When a match is found, the corresponding entry of column 585 is then

5 examined to determine the recipient application. For instance, if the category was Mime Type and the data identifier of the information packet was "IMAGE/JPEG," then application "APP 3" would be selected by the exchange manager.

10 Lastly, at step 625 of Figure 10, the exchange manager 450b then passes the information data packet to the proper recipient application for processing. Using this protocol, the sending application can effectively and efficiently send data wirelessly to a recipient application of a second computer system without any knowledge as to the communication mechanism used.

15 Figure 8B is analogous to Figure 8A, except the receiving computer system 420' includes an externally coupled cell or mobile phone 240c. Also illustrated are the transport library 472b and the telephony manager 474b. The mobile phone 240c can be communicatively coupled to the portable computer
20 via a number of different wired or wireless communication channels, including, for instance, BT, IR, USB or serial as shown. Mobile device 240c then performs the wireless communication 430. It is appreciated that the process of Figure 10 equally applies to system 420' of Figure 8B.

The communication protocol of the present invention affords a very little data consuming computer-to-computer communication protocol that allows the exchange of a little amount of data on a narrow bandwidth wireless network. For example, with this protocol the user has the opportunity to exchange Memos of a hand-held computer using GSM SMS as a transport. Furthermore, the exchange encoding protocol of the present invention offers hand-held developers an opportunity to write wireless data exchanging applications. It is a protocol advantageous for hand-held device communication in that embodiments are simple, convenient, require less data and are flexible. It is transport independent and compliant with current smart messaging devices.

The preferred embodiment of the present invention, a protocol for wireless data exchange via a packet transport based system, is thus described. While the present invention has been described in particular embodiments, it should be appreciated that the present invention should not be construed as limited by such embodiments, but rather construed according to the below claims.